

Indoor unit: V4MDI-36UR

Outdoor unit: U4MRS-36



Function

Design Load

Seasonal Efficiency

Function	YES	Design Load	10.5	Kw	Seasonal Efficiency	SEER	6.3
Cooling	YES	Cooling	10.5	Kw	Cooling	SEER	6.3
Heating / Average Zone	YES	Heating / Average Zone	10.6	Kw	Heating / Average Zone	SCOP(A)	4.1
Heating / Warmer Zone	-	Heating / Warmer Zone	-	Kw	Heating / Warmer Zone	SCOP(W)	-
Heating / Colder Zone	-	Heating / Colder Zone	-	Kw	Heating / Colder Zone	SCOP ^o	-

Cooling

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	Pdc	10.506	Kw
Tj=30°C	Pdc	7.829	Kw
Tj=25°C	Pdc	4.992	Kw
Tj=20°C	Pdc	2.97	Kw

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	EERd	2.66
Tj=30°C	EERd	4.63
Tj=25°C	EERd	7.56
Tj=20°C	EERd	13.5

Heating / Average Zone

Declared capacity for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	9.355	Kw
Tj=2°C	Pdh	5.714	Kw
Tj=7°C	Pdh	3.915	Kw
Tj=12°C	Pdh	4.336	Kw
Tj=bivalent temperature	Pdh	9.355	Kw
Tj=operation limit	Pdh	8.393	Kw

Declared coefficient of performance for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	2.53
Tj=2°C	COPd	3.86
Tj=7°C	COPd	5.75
Tj=12°C	COPd	6.97
Tj=bivalent temperature	COPd	2.53
Tj=operation limit	COPd	2.14

Heating / Warmer Zone

Declared capacity for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	Pdh	-	Kw
Tj=7°C	Pdh	-	Kw
Tj=12°C	Pdh	-	Kw
Tj=bivalent temperature	Pdh	-	Kw
Tj=operation limit	Pdh	-	Kw

Declared coefficient of performance for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	COPd	-
Tj=7°C	COPd	-
Tj=12°C	COPd	-
Tj=bivalent temperature	COPd	-
Tj=operation limit	COPd	-

Bivalent Temperature

Heating / Average Zone	Tbiv	-7	°C
Heating / Warmer Zone	Tbiv	-	°C

Operating Limit Temperature

Heating / Average Zone	Tol	-15	Kw
Heating / Warmer Zone	Tol	-	Kw

Electricity Data

Electric power input in power modes other than 'active mode'

Off mode	P _{OFF}	0.009	Kw
Standby mode	P _{SB}	0.009	Kw
Thermostat off mode	P _{TO}	0.01	Kw
Crankcase heater mode	P _{CK}	0.0	Kw

Annual electricity consumption

Cooling	Q _{CE}	580	kWh/a
Heating / Average Zone	Q _{HE}	3651	kWh/a

Capacity control - Variable

Other Items

Sound power lever (indoor unit)	LWA	58	dB(A)
Sound power lever (outdoor unit)	LWA	66	dB(A)
Global warning potential	GWP	2.088	Kg CO ₂ eq
Rated air flow (indoor unit)	-	-	m ³ /h
Rated air flow (outdoor unit)	-	-	m ³ /h

