

Indoor unit: V4MKI-36

Outdoor unit: U4MRS-36



Function

Design Load

Seasonal Efficiency

Function	Design Load	Seasonal Efficiency
Cooling	10,5 Kw	SEER 6,3
Heating / Average Zone	10,5 Kw	SCOP(A) 4
Heating / Warmer Zone	- Kw	SCOP(W) -
Heating / Colder Zone	- Kw	SCOP© -

Cooling

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	Pdc	10,5	Kw
Tj=30°C	Pdc	7,659	Kw
Tj=25°C	Pdc	4,876	Kw
Tj=20°C	Pdc	2,683	Kw

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	EERd	2,59
Tj=30°C	EERd	4,38
Tj=25°C	EERd	7,41
Tj=20°C	EERd	14,5

Heating / Average Zone

Declared capacity for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	9,289	Kw
Tj=2°C	Pdh	5,654	Kw
Tj=7°C	Pdh	3,649	Kw
Tj=12°C	Pdh	4,372	Kw
Tj=bivalent temperature	Pdh	9,289	Kw
Tj=operation limit	Pdh	8,423	Kw

Declared coefficient of performance for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	2,48
Tj=2°C	COPd	3,87
Tj=7°C	COPd	5,64
Tj=12°C	COPd	6,23
Tj=bivalent temperature	COPd	2,48
Tj=operation limit	COPd	1,95

Heating / Warmer Zone

Declared capacity for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	Pdh	-	Kw
Tj=7°C	Pdh	-	Kw
Tj=12°C	Pdh	-	Kw
Tj=bivalent temperature	Pdh	-	Kw
Tj=operation limit	Pdh	-	Kw

Declared coefficient of performance for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	COPd	-
Tj=7°C	COPd	-
Tj=12°C	COPd	-
Tj=bivalent temperature	COPd	-
Tj=operation limit	COPd	-

Bivalent Temperature

Heating / Average Zone	Tbiv	-7	°C
Heating / Warmer Zone	Tbiv	-	°C

Operating Limit Temperature

Heating / Average Zone	Tol	-15	Kw
Heating / Warmer Zone	Tol	-	Kw

Electricity Data

Electric power input in power modes other than 'active mode'

Off mode	P _{OFF}	0,007	Kw
Standby mode	P _{SB}	0,007	Kw
Thermostat off mode	P _{TO}	0,007	Kw
Crankcase heater mode	P _{CK}	0,0	Kw

Annual electricity consumption

Cooling	Q _{CE}	583	kWh/a
Heating / Average Zone	Q _{HE}	3675	kWh/a

Capacity control - Variable

Other Items

Sound power lever (indoor unit)	LWA	63	dB(A)
Sound power lever (outdoor unit)	LWA	65	dB(A)
Global warning potential	GWP	2088	Kg CO ₂ eq
Rated air flow (indoor unit)	-	-	m ³ /h
Rated air flow (outdoor unit)	-	-	m ³ /h

