

Indoor unit: V4MKI-60

Outdoor unit: U4MRT-60



## Function

## Design Load

## Seasonal Efficiency

Function	YES	Design Load	16	Kw	Seasonal Efficiency	SEER	6,1
Cooling	YES	Cooling	16	Kw	Cooling	SEER	6,1
Heating / Average Zone	YES	Heating / Average Zone	12	Kw	Heating / Average Zone	SCOP(A)	4
Heating / Warmer Zone	-	Heating / Warmer Zone	-	Kw	Heating / Warmer Zone	SCOP(W)	-
Heating / Colder Zone	-	Heating / Colder Zone	-	Kw	Heating / Colder Zone	SCOP <sup>o</sup>	-

## Cooling

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	Pdc	16	Kw
Tj=30°C	Pdc	11,81	Kw
Tj=25°C	Pdc	7,622	Kw
Tj=20°C	Pdc	3,408	Kw

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	EERd	2,45
Tj=30°C	EERd	4,21
Tj=25°C	EERd	7,12
Tj=20°C	EERd	13,74

## Heating / Average Zone

Declared capacity for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	10,689	Kw
Tj=2°C	Pdh	6,57	Kw
Tj=7°C	Pdh	4,244	Kw
Tj=12°C	Pdh	4,349	Kw
Tj=bivalent temperature	Pdh	12	Kw
Tj=operation limit	Pdh	11,92	Kw

Declared coefficient of performance for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	2,71
Tj=2°C	COPd	3,75
Tj=7°C	COPd	5,43
Tj=12°C	COPd	6,54
Tj=bivalent temperature	COPd	2,38
Tj=operation limit	COPd	2,05

## Heating / Warmer Zone

Declared capacity for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	Pdh	-	Kw
Tj=7°C	Pdh	-	Kw
Tj=12°C	Pdh	-	Kw
Tj=bivalent temperature	Pdh	-	Kw
Tj=operation limit	Pdh	-	Kw

Declared coefficient of performance for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	COPd	-
Tj=7°C	COPd	-
Tj=12°C	COPd	-
Tj=bivalent temperature	COPd	-
Tj=operation limit	COPd	-

## Bivalent Temperature

Heating / Average Zone	Tbiv	-7	°C
Heating / Warmer Zone	Tbiv	-	°C

## Operating Limit Temperature

Heating / Average Zone	Tol	-15	Kw
Heating / Warmer Zone	Tol	-	Kw

## Electricity Data

Electric power input in power modes other than 'active mode'

Off mode	P <sub>OFF</sub>	0,01	Kw
Standby mode	P <sub>SB</sub>	0,01	Kw
Thermostat off mode	P <sub>TO</sub>	0,01	Kw
Crankcase heater mode	P <sub>CK</sub>	0,0	Kw

Annual electricity consumption

Cooling	Q <sub>CE</sub>	918	kWh/a
Heating / Average Zone	Q <sub>HE</sub>	4200	kWh/a

## Capacity control - Variable

Other Items

Sound power lever (indoor unit)	LWA	70	dB(A)
Sound power lever (outdoor unit)	LWA	75	dB(A)
Global warning potential	GWP	2088	Kg CO <sub>2</sub> eq
Rated air flow (indoor unit)	-	-	m <sup>3</sup> /h
Rated air flow (outdoor unit)	-	-	m <sup>3</sup> /h

